

Swing-out rotor, 6-place

Swing-out rotor, 8-place



±90°

n = 4,000 min⁻¹
max. RCF 2,701












±90°





n = 4,000 min⁻¹
max. RCF 2,415






























Swing-out rotor 1324

Cat. No. (with carriers) 1619

Cat. No. (without carriers) 1611

capacity in ml	15	50	12	50
Ø x L in mm	17x120	29x115	17x100	29x115
Cat. No.	0509	0513	-	-
 carrier Cat. No. 1398				
				
Cat. No.	1483A	1484	1482A	1484⁴⁾
boring Ø x L in mm	17x100	30x98	17.5x81	30x98
tubes per rotor	16	4	16	4
max. RCF ²⁾	2,612	2,576	2,522	2,576
radius in mm	146	144	141	144
run-up in sec	27			
run-down in sec, braked	30			

capacity in ml	15	50
Ø x L in mm	17x120	29x115
Cat. No.	0509	0513
 rotor Cat. No. 1619		
		
Cat. No.	1462-A	-
boring Ø x L in mm	17 x 84	30x 87.5
tubes per rotor	6	
max. RCF ²⁾	2,701	
radius in mm	151	
run-up in sec	22	
run-down in sec, braked	25	

capacity in ml	5	6	7	10	15	2.6-3.4	2.7-3	4-5.5	4.5-5	7.5-8.5	1.6-5	4-7	4-7	8.5-10	
Ø x L in mm	12x75	12x82	12x100	17x70	13x100	17x100	13x65	11x66	15x75	11x92	15x92	13x75	13x100	16x75	16x100
Cat. No.	0553²⁾	0501²⁾	0578²⁾	2079	-	0518²⁾	blood collection/urine tubes								
 rotor Cat. No. 1611															
															
Cat. No.	1131	1643	1132	1643	1644	1131	1132	1643	1644	1131	1643	1132	1644		
boring Ø x L in mm	13 x 53	13.2x 81	17.5 x 53	13.2x 81	17.5 x 81	13 x 53	17.5 x 53	13.2 x 81	17.5 x 81	13 x 53	13.2 x 81	17.5 x 53	17.5 x 81		
tubes per rotor	8														
max. RCF ²⁾	1,914	2,415	1,914	2,415	1,914	2,415	1,914	2,415	1,914	2,415	1,914	2,415	1,914	2,415	
radius in mm	107	135	107	135	107	135	107	135	107	135	107	135	107	135	
run-up in sec	22														
run-down in sec, braked	25														

⁵⁾ Tested by the TÜV in conformity with DIN EN 61010, section 2-020.

⁶⁾ A rubber stopper for closing the tube is available under Cat. No. 0535.
The tube may not be centrifuged with the stopper. The stopper only serves to close the tube for agitating or mixing.